

High Temperature Mineral Insulated Probe



(-200 ??? 1100 ° C) ?????? ?????????????? ?????????? ?????????? ?????? ?. ?????????? Ø1.5mm ?????????? 3 ???? ?????????? ??????????: - 180, 500, 1000 mm ??????? 1.0 ? ?????? ?????????????? -200 ??? 1100 °C ??????? ?? ?????????????? ?????? ?????????? ????????? ?? BS EN 60584-1:2013

?????????: ??? ?????????????? ??????
?????
???? ?? ??????? 68,80 €

???? ??????? 85,31 €

???? ??????? ?????? ??? 68,80 €

???????

????????? ?????? 16,51 €

[?????? ?? ?? ?????](#)

?????????

High Temperature Mineral Insulated Probe

????? ?????????????? ?????????? ??????????.

????????? ?????????? ?? ?????? ?? ?????? ?? ?????????? ?????? ?????? ?? ?????????? ?? ?????????? ???. (Flexible mineral insulated (MI) probe)

????????? ?? ?? ?????? ?? ?????? ??????????????. ? ?????? ?????????? ?????? ?????????? ?? ?? ??????????????. ?????? ??????????????: -200 ??? 1100°C. ?????????????? ??????? PTFE 2.00 m. ?????????? ??????????: Ø1.5mm
????????? 3 ???? ?????????? : - 180, 500 (75.13 €), 1000 mm (81.34 €)

Data sheet

Probe $\pm 1.5\text{ }^{\circ}\text{C}$ between $-40\text{ }^{\circ}\text{C}$ &
Accuracy $375\text{ }^{\circ}\text{C}$, $\pm 0.4\%$ between
(Type K): $375\text{ }^{\circ}\text{C}$ & $1000\text{ }^{\circ}\text{C}$
Probe -200 to 1100°C
Range:
Probe less than 2 seconds
Response
Time:
Probe 1.5 mm
Diameter:
Probe 180, 500 or 1000 mm
Length: