

?? ??????? ?????????????? ?????????



?? ?????? ?????????????? ?????????? ?????????????? ?????????????? ?????? ?????? - ?????????????? ??? ?? ?????????? ??? ?????????????????? ?????????????? ??? ?????????? ?????? ?????????????, ?????????????? ??? ??? ?????????? ?????????????????? ??? ?????? ??? ?????????????????? ??? ??? ?????????????????? / ?????????, ?? ?????????, ?????????????????, ?????????????, ??????????, ?????????????????? ?.??.

?????????????: ??? ?????????????????? ???????

?????

????? ?? ?????????? 39,00 €

????? ?????????? 48,36 €

????? ?????????? ?????? ?????? 39,00 €

?????????

????????????? ?????? 9,36 €

[????????? ??? ?? ?????????](#)

?????????????

?? ??????? ?????????????? ?????????

????????????????? ?????????????? ?????? ?????? - ?????????????? ??? ?? ?????????? ??? ?????????????????? ?????????????? ??? ?????????? ?????? ??? ??????????, ?????????????? ??? ??? ?????????? ?????????????????? ??? ?????? ??? ?????????????????? ??? ??? ?????????????????? / ?????????? ??? ??? ?????? ?? ?????????, ?????????????????, ??????????, ??????????, ?????????????? ?.??.

- CE 1639 approved device
- professional medical device
- easy-to-use, no complicated instructions
- quick one-second readings

- audible beep when reading taken
- accurate oral-equivalent temperature readings
- audible high temperature alert and mute setting
- bright, blue LED backlight
- memory function (stores last 25 readings)
- class II medical device
- supplied with full one year guarantee

range - forehead mode:	34 to 42.2 °C (93.2 to 108 °F)
range - surface mode:	-22 to 80 °C (-7.6 to 176 °F)
operating range:	10 to 40 °C (50 to 104 °F), 15 to 85 %rh
storage range:	-20 to 50 °C , less than 85 %rh
resolution:	0.1 °C/°F
accuracy - forehead mode:	±0.2 °C (0.4 °F) within 35 to 42 °C (95 to 107.6 °F). Otherwise ±0.3 °C (0.5 °F)
accuracy - surface mode:	±0.3 °C (0.5 °F) with 22 to 42.2 °C (17.6 to 108 °F). Otherwise ±4% or ±2 °C (±4 °F), whichever is greater
emissivity:	Fixed at 0.95 in Surface Mode
battery:	2 x AAA Alkaline (Supplied)
battery life:	3000 hours (auto-off after 60 seconds)
display:	LCD with backlight
backlight:	Yes
dimensions:	40.2 x 48 x 158 mm
weight:	100 grams
case material:	ABS plastic
guarantee:	one year
measurement scale:	Celsius/Fahrenheit
conforms to standard:	CE 1639