

STM – Smart Tool Digital Inclinator Module, 360°



Smart Tool Digital Inclinator Module, 360°. 360° measurement range, displays to 0.05° @ 0° and 90°, 0.1° all other angles. Switchable reading between degrees, % slope and pitch (rise over run) in mm/m. Switchable beeper sounds when SmartTool is level. Tough durable construction suitable for use on site

?????????: ??? ?????????? ?????

????

???? ?? ?????? 149,19 €

???? ?????? 185,00 €

???? ?????? ?????? 149,19 €

???????

????????? ?????? 35,81 €

[????????? ??? ?? ??????](#)

?????????

STM – Smart Tool Digital Inclinator Module, 360°

Features

- 360° measurement range, displays to 0.05° @ 0° and 90°, 0.1° all other angles
- Switchable reading between degrees, % slope and pitch (rise over run) in mm/m
- Switchable beeper sounds when SmartTool is level.
- Tough durable construction suitable for use on site

Applications

- Measuring or setting the pitch of drainage pipes
- Setting or checking the angle of disabled access ramps

- Setting or checking the grading of ground or roads for drainage

Parameter	Value	Unit	
Number of Axis	1		-
Range	360		°
Resolution	0.05 @ 0° & 90°, 0.1 all othe angles		°
Accuracy at 20°C	±0.05 Level, ±0.05 Plumb, ±0.2 other		°
Display Type	LCD		-
Output Format	-		-
Power Source	PP3 (9V) Battery		-
Frequency Response	1		Hz
Technology	Liquid filled capacitive		-

Download

[SmartTool Calibration](#)

[RoHS Certificate](#)

[REACH Certificate](#)

[Conflict Minerals Certificate](#)