

WiFi ?????????????? ??? ?????????? ??? ??????????



WiFi ?????????????? ??? ?????????? ??? ??????????. ThermaData Pharm vaccine data loggers. / ThermaData Pharm WiFi ?????????????? ??? ??????????,
????????? ??? ?????????????? ??????????????. ??????? ??????????? ?????? ??????????? ?????? ?????????????? ?????????? ??????????????
????? ??????????????. ????????? / ?????????? ?????????????????? ?????? email ??? SMS. ??????? ?????????????? ?????????????????? ??????????????????

?????????????: ??? ?????????????????? ???????
?????

[????????? ??? ?? ????????](#)

????????????

WiFi ?????????????? ??? ?????????? ??? ??????????

ThermaData Pharm WiFi ?????????????? ??? ??????????, ?????????? ??? ?????????????????? ???????????????.

?? ??????????????? ??????????? ThermaData Pharm WiFi ?????? ??? ?????????????? ??? ??????????? ?????????? ?????????????????? ?????????????????? ???
?????????????? ?? ?????????????? ?????????????????? ?????????????????? ??? ?????????????? ?????????? ??????????????????, ?????? ??????????, ?????????? ??? ?????????? ??????????. ??
ThermaData Pharm ?????????????? ?? ??? ??????????, ?? TD1F-PHM ?? ?????? ?????????????? ??? ?????? ?????????????? ?????????????? ? ?? TD2F-PHM ??? ?????
????? ?????????????????? ??????????????????

Each unit has an intuitive LCD displaying; temperature, WiFi connection status, max/min recorded temperatures, alarm status and battery life.

Simple to set up, the logger once up and running will transmit recorded data to a WiFi router connected to the internet which can then be accessed and viewed from a PC, laptop or tablet anywhere in the world.

At programmable intervals, the loggers will record temperature from both sensors, recording up to a maximum of 18000 readings (9000 from each sensor). Each logger incorporates a red and green LED. The flashing green LED indicates that the logger is active/logging and the flashing red LED indicates that the customised preset alarms have been exceeded. Each logger communicates directly to the WiFi router at set intervals to push data through the internet into ThermaData Studio. The information is available to be analysed and exported into a report format. Each unit is supplied with a USB lead, wall bracket and FREE ThermaData Studio software (licence free)

available to download from our website.

Each thermistor probe is encased in a sealed bottle and incorporates a two metre PUR/PVC fixed lead. To begin monitoring, simply unscrew and top up with Glycol solution (50ml bottle supplied). Please Note: Model TD1F is supplied with one external remote probe and an internal sensor. Model TD2F is supplied with two external remote probes. For more information contact our sales office.

How does the ThermaData Pharm WiFi logger work?

Using the unique ID of each logger ThermaData Studio creates a secure connection between logger and software which can be accessed and viewed anytime and anywhere with an internet connection.

Each logger communicates directly to the WiFi router at set intervals to push data through the internet into ThermaData Studio.

The information is available to be analysed and exported into a report format.

ThermaData Studio Software

Both powerful and sophisticated, yet user-friendly, the ThermaData Studio software enables temperature data to be organised and analysed to provide management information.

The ThermaData Studio software has the ability to display up to 32 traces on a graph, the trace colours are user selectable. All files can be viewed as thumbnail icons for easy identification.

The software allows the user to programme the logging sample/interval rate (0.1 to 330 minutes), communication interval (sync) with PC, real-time clock, °C or °F and a manual start option. It is also possible to include a user ID for each logger.

You can read some informative and useful information about our Thermadata Studio software, along with a set-up guide by clicking links:

[ThermaData Studio Walk Through Setup Guide](#)

[Thermadata Studio Auto Archive Feature](#)

[ThermaData Studio Viewing & Exporting Data & the TDLink iOS App](#)

?????????????

range internal:	0 to 50 °C (TD1F only)
range external:	-40 to 70 °C
resolution:	0.1 °C/°F
accuracy:	±0.5°C
memory:	2 x 9000 readings
sample rate:	6 seconds to 330 minutes
battery:	2 x 1.5 volt AA
battery life:	approximately 12 months
display:	12 mm LCD/2 LED's
dimensions:	29 x 72.5 x 96mm
weight:	165 grams
case material:	ABS plastic
country of manufacture:	United Kingdom
guarantee:	two years
measurement scale:	Celsius/Fahrenheit